

Product Profile

- Modular design minimizes operator visual obstruction
- Small size and flexible mounting
- Shock, temperature and environmental protection
- Configurable according to user requirements
- Supports industry standard communications and 2.4 GHz or 802.11b 11Mbps radio



2 4 5 5 VEHICLE MOUNT COMPUTER

The 2455 is a versatile, high performance and economical solution for data collection applications using industrial vehicles such as forklift trucks and stock pickers.

The two piece design of the terminal allows the operator to separate the display and keyboard or conventionally mount as one unit. The modularity and small size easily adapts to space constraints common with today's smaller forklifts. Unique bracket design on the terminal provides unlimited viewing angle and positioning choices.

Industrial casing protects the terminal from dust, dirt and rain. The 2455 can tolerate very cold temperatures outdoors or usage in freezers. Wide ranging power supply options make installation in virtually all industrial vehicles easy. The

2455 is built to sustain real-world conditions such as constant shock, vibrations and power fluctuations common to industrial vehicles.

The terminal integrates with most common host environments, either directly to the network, or through a data collection server which provides additional network management benefits. IBM and VT terminal emulation eliminates the need to re-program host applications. In addition, TCP/IP network support provides similar ease of integration in client/server environments.

The 2455 incorporates 2.4 GHz and 802.11b 11Mbps radio support for wide area coverage and interference immunity and interoperability with other WLI Forum OpenAir products.

Physical Characteristics

Display Unit: 28.4 x 15.2 x 10.7cm (11.2" x 6" x 4.2") 4.04kg (8.9lbs)
Keyboard: 28.4 x 10.4 x 4.3cm (11.2" x 4.1" x 1.7") 1kg (2.2lbs)
Power Supply: 16.5 x 11.4 x 2.5cm (6.5" x 4.5" x 1") .73kg (1.6lbs)

Environment

Operating Temperature:
Standard Unit -10° to +50°C (14° to 122°F)
Cold Temperature Option:
-30° to +50°C (-22° to 122°F)
Storage Temperature:
-20° to 60°C (-4° to 140°F)
Humidity: 10 to 90% non-condensing
Shock & Vibration: Vibration tested to SAE J-1399 Class 2, MIL STD 810D
Sealing: Sealed against dust and moisture to NEMA 3 and IP54

Power

Primary: 12V to 80VDC universal power supply with surge, over-voltage, and reversal protection
Memory Backup: Rechargeable NiCad

Memory

RAM Memory: 1MB
Non-volatile Memory: 2MB Option for 2MB additional, 4MB total
Extended Storage: 2, 4MB SRAM

Interfaces

Local Device Communications:
Auxiliary RS-232
Laser Scanners: 10-pin connector for use with Intermec cabled & wireless laser scanners

- Optical Serial Interface
- RS232-C up to 38.4 baud
- XMODEM, YMODEM for data transfer
- Supports Configurable Serial Protocol and XON/OFF

Display

Full Screen: 25 lines by 80 characters or configurable oversized characters including 13 x 80, 25 x 40, or 13 x 40
Display Options: Transmissive LCD CGA display for standard environments
 EL (electroluminescent) CGA display for cold or bright locations

Keyboard

Layout: ABCD keyboard layout with five function keys, oversized numeric keypad

- F1-F10 function keys also available on display unit
- Standard PC-AT keyboard interface for optional keyboards (req. adapter cable)
- Options for U.S. Multilingual, European, IBM 5250, IBM 3270, and ANSI/VT

Software

Programmable: Microsoft C
Terminal Emulation: IBM 3270 and 5250 SNA and TELNET, ANSI/VT, TN5250, TN3270, Screen Mapping
Web-based: dcBrowser™ for HTML applications

Connectivity

- DHCP Client
- Direct TCP/IP Support
- Sockets interface or terminal emulation
- Network Ethernet or Token Ring

Integrated RF Module

Frequency: 2.4 GHz frequency band, actual frequencies in use vary by country
WLI Forum OpenAir
Type: Frequency Hopping Spread Spectrum
Data Rate: 1.6 Mbps, .8 Mbps fallback
Range*: From 1500+ ft (450+ m) to 500 ft (150 m) depending on environment

IEEE 802.11b Wi-Fi Certified

Type: Direct Sequence Spread Spectrum
Data Rate: 11/5.5/2/1 Mbps with Auto fallback for increased range
Range* at 1 Mbps: From 1750 ft (533 m) to 165 ft (50 m) depending on environment
Range* at 11 Mbps: From 525 ft (160 m) to 80 ft (24 m) depending on environment
Security: Wired Equivalent Privacy (WEP) - 64 or 128 bit encryption
 *Unlimited range with roaming

Host Support via DCS 300 Server

Host Environment: IBM AS400, 5/390, Digital, HP, Unix, Windows NT
Connectivity: Ethernet, Token Ring, 100BaseT, Twinax, Coax, SDLC
Communications: TCP/IP, SNA

Accessories

Desktop stand, Desktop power supply, User's Manual, Programmer's Software Kit (PSK), EZBuilder™ Rapid Application Development Software

Regulatory Approvals

FCC - Part 15.247 Certified, Canada - RSS 210 Certified, ETS 300 328 Type Approved, EN 55022 / CISPR 22 Class B, FCC Part 15 & ICES-003 Class A, SCT Certified, NOM - EM-121, pending, AS 3548 - C tick Marked, Compliant with all European Directives, CE Marked (prETS 300 826), UL Listed, UL 1950, C22.2 #950 & IEC 60529-IP54, TUV Licensed, EN 60950 & EN 60529 - IP54, NYCE Certified, NOM 19

Intermec reserves the right to make changes without notice to any products herein for any reason at any time, including but not limited to improving the reliability, form, fit, function or design. Please contact Intermec for current price list and availability.



The Standard for
Wireless Fidelity.

North America

Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
tel: 425.348.2600
fax: 425.355.9551

Systems & Solutions

550 2nd Street S.E.
Cedar Rapids, Iowa 52401
tel: 319.369.3100
fax: 319.369.3453

Media Supplies
9290 Le Saint Drive
Fairfield, Ohio 45014
tel: 513.874.5882
fax: 513.874.8487

**Europe/
Middle East & Africa**

Headquarters
Sovereign House
Vastern Road
Reading, Berkshire RG1 8BT
United Kingdom
tel: +44.118.987.9400
fax: +44.118.987.9401

Gothenburg
Idrottsvägen 10
P.O. Box 123
SE-431 22 Mölndal
Sweden
tel: +46.31.869500
fax: +46.31.869595

**Asia/
Latin America**

Hong Kong
26-12 Shell Tower
Times Square
1 Matheson Street
Causeway Bay
Hong Kong
tel: 852.2574.9777
fax: 852.2574.9725

Singapore
25-16 International Plaza
10 Anson Road, 079903
tel: 65.324.8391
fax: 65.324.8393

Australia
Level 7, 200 Pacific Highway
Crows Nest NSW 2065
Australia
tel: 61.2.9901.2065
fax: 61.2.9954.6300

South America and Mexico
17921 B Skypark Circle
Irvine, California 92614
tel: 949.442.9393
fax: 949.757.1687

**Worldwide
Fax Document
Retrieval Service**
800.755.5505
(North America Only)
tel: 650.556.8447

Internet
www.intermec.com

Sales
800.347.2636
(toll free in N.A.)
tel: 425.348.2726

Service and Support
800.755.5505
(toll free in N.A.)
tel: 425.356.1799

Copyright © 2001 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 608454-01B 10/01

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.